

# A Bellbox with "Universal" Approval

## Vortex II

*External Alarm Housing*

A stylish design, easy to install and loaded with all the features any alarm engineer could require. The Vortex II is suitable for all external and internal applications. Constructed in polycarbonate with a 115dB sounder output, the Vortex II complies with the latest EN50131-1; Group 3, Class 4.

- Protective inner skin
- 115dB Sounder
- Anti-Tamper Protection
- Intelligent Strobe saver
- Twin comfort LED's
- Battery charge indicator
- SAB and SCB Modes
- Total Polycarbonate Construction
- Dummy Version (LY52-056-49)

### Specification

Hold Off Supply:	12V DC
Standby Current:	20mA
Siren Current:	180mA
Strobe Current:	120mA
Siren Output:	115dB
Lens Colour:	Blue
Weight:	720g
Dimensions:	340 x 200 x 73mm



Vortex II - LY52-055-48



Lynteck, Churchill Way, Nelson, Lancashire BB9 6RT email: [sales@lynteck.co.uk](mailto:sales@lynteck.co.uk)  
[www.lynteck.co.uk](http://www.lynteck.co.uk) Tel: 01282 717 490 Fax: 01282 698 020  
Technical Support (Mon-Fri 9am-5pm): 0906 711 2329 (calls charged at 50p per min)  
Company policy is one of continuous improvement,  
we reserve the right to change specification without prior notice.

