



This small active stereo cabinet loudspeaker set has been designed for the Audio-Video market.

The SDX5P set consists of an active and passive loudspeaker. The active loudspeaker is equipped with a stereo amplifier with volume and bass-treble tone control. The passive loudspeaker is linked via the push terminals.

The SDX5P set can easily be mounted next to the projection screen. The audio signal of the portable PC or LCD/DLP projector is plugged into the active loudspeaker, what gives you an easy to use and compact system solution. SDX5P loudspeakers can also be used for mobile presentation purposes, monitoring,...

The loudspeakers are provided with a metal U-bracket for easy mounting.

It is available in black (Ref.: SDX5P-BL) and white (Ref.: SDX5P-W)

TECHNICAL SPECIFICATIONS

Type	Active 2-way HiFi Pro, sealed box
Cabinet	ABS
Woofer	5.3" PP Shielded
Tweeter	1" mylar shielded
Impedance	4 Ohm/channel
RMS Power 4 Ohm	Build in amplifier
AES Rated	2 x 25 watt
Dynamic Peak (lo-cut)	2 x 40 watt
SPL 1 watt/1 m	89 dB
SPL Max peak	105 dB
Frequency Range	65 Hz - 20 kHz (bass-treble tone control)
Dispersion	80° H x 80° V
IP rating	Indoor use only
Dimensions (H x W x D)	243 x 180 x 148 mm
Weight Active Loudspeaker	3.15 Kg
Passive loudspeaker	2.25 Kg