

CLS1

The Ampetronic CLS1 is the first in a series of induction loop drivers aimed at the demands of the electrical and audio-visual contractor.

Designed for simple discrete installation, the CLS1 offers the most cost effective and capable solution in its class. The amplifier is very compact and designed specifically for wall mounting. All connections and controls are secured behind a tamper resistant, hinged, detachable cover. Combined with its small size, the range of mounting and cabling options ensure that installation is convenient and tidy in any environment. Input options are comprehensive, with three independent inputs for balanced microphone, balanced and unbalanced line, low impedance and 100V - line speaker systems.

Backed up by Ampetronic's standard 5 year warranty and comprehensive support services, the CLS1 is truly fit and forget.



Features

- Quick and simple to install
- Area coverage to >200m²
- 3 independent configurable inputs
- Wall mounted
- Metal Loss Correction
- 5 Year warranty
- Cabling and controls behind tamper resistant cover
- Free Technical support

Applications include:

- Community Centres
- Board rooms
- Churches
- Interview rooms
- Meeting rooms
- Classrooms

Perimeter Loops– Area Coverage (maximum)

Room aspect ratio	1:1	2:1	3:1
Maximum area m ²	120	150	200

For any induction loop system, area coverage is dependent on several factors. Please check these assumptions and contact Ampetronic for advice if required.

- Loop must be 1 – 2 m above or below the receiver height
- There should be no metal structures in the plane of the loop
- Sufficient voltage to drive the loop – check the table below

Maximum Cable Length

The CLS1 is designed for SINGLE TURN loops for optimum audio quality:

- Loops with DC resistance from 0.2Ω
- Impedance up to a maximum of 1.8Ω

Maximum cable length is dependent on cable type and on the application

Cable type	Maximum Cable Length (m)	
	Normal Use	Transient Speech
1.0mm ² copper	68	79
2.5mm ² copper	93	118
4mm ² copper	97	126
1.8mm ² flat copper tape	120	136

CLS1 Product Information

The CLS1 enclosure is designed for simple, permanent installation, with secure lid protecting connections and controls, while leaving operation indicators visible. The case is designed to make access simple, and to ensure the amplifier can be installed in the most constrained spaces.

Mounting

Designed for vertical panel mounting using 4 screws (6 holes provided). Template for screw placements provided. The CLS1 is compact enough to fit on a 1U rack tray with feet removed.

Enclosure access

Hinged lid, secured by 2 Phillips PH2 screws. Lid can be removed completely if required, for ease of access, or if there is no room to hinge the lid forwards.

Cable routing

Knock-outs (diameter 20mm) are provided for routing cables into the enclosure. 2 on the top edge, 4 on on the rear face, 4 on the bottom edge, providing excellent installation flexibility.

Cable connections

All input cable connections are made with screw terminals mounted on one side of the PCB. Mains power connections are made to a chassis mounted screw terminal block. Loop connection is made to a screw terminal pair mounted on the PCB. Cable connections are illustrated on a detailed label on the case interior.

Indicators

3 LED indicators are visible with the case open or closed:

- AGC Amber LED lit when input signal is activating the automatic gain control
- Current Green LED lit when current is running in the loop
- Power Green LED lit when the unit has power

Controls

Five controls are located to be accessed only with the lid open, all screwdriver adjustable.

- Level controls for inputs 1, 2 and 3
- Metal loss correction
- Loop drive current



INPUTS

Input 1	Balanced Mic, balanced or unbalanced line Input impedance 10k Ω per side Min level (MIC / Line) -73dBu / -31dBu Max level (MIC / Line) -37dBu / +5dBu Phantom voltage MIC only +12V
Input 2	Balanced or unbalanced line, expansion port Input impedance 1M Ω per channel Min level -33dBu Max level +3dBu
Input 3	Isolated 100V line or low impedance mono or stereo speaker Input impedance 100V Line / spkr 120k Ω / 7.8k Ω Min level 100V Line / spkr +14dBu / -9dBu Max level 100V Line / spkr >+47dBu / >+27dBu
AC power input supply	230V 30W 45-65Hz 110V option available Connected via chassis mounted screw terminal block
Input fuse	T250mA

OUTPUTS

Drive Voltage	>6.4V _{RMS} - 9.0V pk
Drive Current	Continuous 1kHz sine wave >3.3A _{RMS} 5.0Apk Short term peaks >5A _{RMS} 7Apk
Minimum Loop Resistance	0.2 Ω
Maximum Loop Impedance	1.5 Ω

AUDIO SYSTEM

Frequency Response	80Hz to 6.3kHz \pm 3dB
Distortion	THD+N <0.5% 1kHz sine at 1.66A _{RMS}
Automatic Gain Control (AGC)	Optimised for speech. Dynamic range >36dB
Metal loss correction (MLC)	0 to 3dB per octave frequency correction (1kHz remains constant). Control mounted on PCB.

PHYSICAL

Cooling	Natural convection
Environment	IP20, -10°C to +40°C
Dimensions	W, H, D: 200mm, 200mm, 44mm
Weight	1.8kg
Mounting	Wall mounting, secured by 4 screws

Standards Compliance

The CLS1 is CE marked to all relevant safety and EMC standards, including EN60065 and EN55103. Safe operation is subject to correct installation. The CLS1 will meet the requirements of IEC60118-4 and the relevant recommendations of BS7594 if specified and installed correctly.

AMPETRONIC



Issue no UP36402-1

www.ampetronic.com
sales@ampetronic.com
support@ampetronic.com
phone +44 (0)1636 610062
fax +44 (0)1636 610063

Northern Road, Newark NG24 2ET. United Kingdom

DISTRIBUTOR