



PRO47T

Thread mounted gooseneck condenser (315mm long)



PRO47TL

Thread mounted gooseneck condenser (401mm long)

PRO 47T / PRO 47TL SPECIFICATIONS

ELEMENT	Fixed-charge back plate permanently polarized condenser	
POLAR PATTERN	Cardioid (Unidirectional)	
FREQUENCY RESPONSE	70-16,000 Hz	
OPEN CIRCUIT SENSITIVITY	- 37 dB (14.1 mV) re 1V at 1 Pa*	
IMPEDANCE	100 ohms	
MAXIMUM INPUT SOUND LEVEL	134 dB SPL, 1 kHz at 1% T.H.D.	
SIGNAL TO NOISE RATIO	66 dB, 1 kHz at 1 Pa*	
DYNAMIC RANGE (TYPICAL)	106 dB, 1 kHz at Max SPL	
PHANTOM POWER REQUIREMENTS	9-52V DC, 2 mA typical	
WEIGHT (LESS CABLE)	PRO 47T	63 grams
	PRO 47TL	67 grams
DIMENSIONS	PRO 47T	315.0 mm long
	PRO 47TL	401.0 mm long
	Both	12.0 mm head diameter
OUTPUT CONNECTOR	3-pin XLRM-type	
CABLE	3.0 m long (permanently attached to microphone), 2.6 mm diameter 2-conductor, shielded cable	
ACCESSORIES FURNISHED	AT8146 foam windscreen, AT8425 5/8" -27 threaded mounting stud	

* 1 Pascal = 10 dynes/cm² = 10 microbars = 94 dB SPL

