

LTC 0355 Series Monochrome Cameras



Security Systems



- 1/3-inch Format CCD Imager
- High Sensitivity
- Advanced Digital Signal Processing
- High Resolution
- Auto Detection of Lens Type
- Easy to Install
- Accepts AC or DC Voltages

Lens not included

The LTC 0355 series are compact rugged, 1/3-inch image format digital monochrome CCD cameras. Their superior sensitivity and resolution provide optimal performance in virtually all environments. This fully automatic camera is ready to work for you, and is easy to install in even the most demanding applications. On-screen Displays (OSD) provide quick and easy access to all camera features.

The LTC 0355 cameras also comes with a lens wizard that automatically detects the type of lens installed and provides an OSD guide that allows the installer to easily adjust the lens level and focus without special tools or filters.

The ability to operate on AC or DC provides added flexibility to system designs and reduces the amount of training and support items to keep on-hand. Easy Installation, digital signal processing, on screen displays, superior picture quality and reliability brings the video performance of standard resolution monochrome cameras to a level never reached before. The LTC 0355 series is the best choice for first time and professional users.

Bilinx Technology

The LTC0355 series cameras incorporate Bilinx. Bilinx is a bi-directional communication capability embedded in the video signal of all Bosch Dinion cameras. With Bilinx technicians can check status, change camera settings and even update firmware from virtually anywhere along the video cable. Bilinx reduces service and installation time, provides for more accurate set-up and adjustment, and improves overall performance. In addition, Bilinx uses the standard video cable to transmit alarm and status messages, providing superior performance without additional installation steps.

SPECIFICATIONS

Electrical

Model No.	Rated Voltage	Voltage Range	System
LTC 0355/10	12 VDC 24 VAC, 50 Hz	10.8-39 VDC 12-28 VAC, 45-65 Hz	CCIR
LTC 0355/20	12 VDC 24 VAC, 60 Hz	10.8-39 VDC 12-28 VAC, 45-65 Hz	EIA
LTC 0355/50	230 VAC, 50 Hz	85-265 VAC, 45-65 Hz	CCIR
LTC 0355/60	120 VAC, 60 Hz	85-265 VAC, 45-65 Hz	EIA

Power Consumption: 4 W, excluding lens.

Imager: Interline transfer CCD, 1/3-inch image format.

Active Picture Elements:

CCIR Models: 752 H x 582 V.

EIA Models: 582 H x 494 V.

Sensitivity (3200 k):

		Usable Picture (50 IRE)	Full Video
Scene illumination ¹⁾	fc	0.009	0.036
	lx	0.09	0.36
Imager illumination	fc	0.0018	0.0072
	lx	0.018	0.072

1) for f/1.2 lens, 89% scene reflectance.

Horizontal Resolution: 570 TVL.

Signal-to-noise Ratio: 50 dB.

AGC: 21 dB, (max).

Electronic Shutter: Automatic, 1/50 to 1/500000 sec. (CCIR),
1/60 to 1/600000 sec. (EIA)

Aperture Correction: Horizontal and vertical
symmetrical.

Backlight Compensation: Center window weighting.

Video Output: Composite video 1.0 Vpp, 75 Ohms.

Synchronization:

Line-Lock : (When powered by AC only) Synchronizes
the camera to the power line zero crossing
for roll-free vertical interval switching.
Vertical phase delay can be adjusted
(0 - 358 degrees) to allow vertical
synchronization in multi-phase power
installations.

Crystal-Lock: (When DC-supply or L/L off) Internal crystal
reference is standard on all models.

Controls

Video level

Shutter: AES/Off/Flickerless

AGC: On/Off

BLC: On/Off

Auto Black: On/Off

Vphase Adjustment: 0 - 358 degrees

MECHANICAL

Connectors: - Video Output: BNC.

- Video/DC-Iris connector: 4-pin EIA-J.

Power: LTC 0355/10 and LTC 0355/20: push type
connectors, polarity

independent, isolated from video output
terminals

LTC 0355/50: 2-wire power cord with Euro
plug

LTC 0355/60: 2-wire power cord with
polarized plug

Camera mounting: Top and Bottom, 1/4-inch
20 UNC.

Lens Mounting: C and CS.

Dimensions: (HxWxD*) 58 x 66 x 122 mm
(2.28 x 2.6 x 4.8 inch). *including connectors.

Weight: 0.45 kg (0.99 lb).

ENVIRONMENTAL

Temperature Range: Operating: -20 to 50°C (-4 to 122°F).

Storage: -25 to 70°C (-13 to 158°F).

Operating Humidity: 5% to 93% non-condensing.

Electromagnetic Compatibility:

EMC immunity: According EN50130-4

EMC emission: According EN505022

class B,

According FCC, class B part 15

Safety: LTC 0355/10 and LTC 0355/50: EN60065

LTC 0355/20 and LTC 0355/60: UL6500

Accessories

Lenses DC-Iris:

LTC 3364/40: 2,8 - 12 mm, F1,4 - F360.

LTC 3374/20: 5 - 50 mm, F1,4 - F185.

Power Transformers and Power Supplies:

Model No.	Rated Input	Rated Output
TC1334	120 VAC, 60 Hz	24 VAC, 30 VA
TC120PS	120 VAC, 60 Hz	15 VDC, 9 VA
TC220PSX-24	220 - 240 VAC, 50/60 Hz	24 VAC, 20 VA
TC220PS	220 - 240 VAC, 50/60 Hz	15 VDC, 9 VA

Bosch Security Systems.
5600 JB Eindhoven
The Netherlands
Tel: +31 (40) 27 80000
Fax: +31 (40) 27 80001
www.boschsecuritysystems.com

BOSCH